

## 2. Lexical Analysis

### 2.1 Tasks of a Scanner


### 2.2 Regular Grammars and Finite Automata

### 2.3 Scanner Implementation

# Tasks of a Scanner



## 1. Recognizes tokens



## 2. Skips meaningless characters

- blanks
- tabulator characters
- end-of-line characters (CR, LF)
- comments

# Why is Scanning not Part of Parsing?



**Tokens have a syntactical structure, e.g.**

```
ident = letter {letter | digit | '_'}.  
number = digit {digit}.  
if =      "|" "f".  
eq| =     "=" "=".  
...
```

Why is scanning not part of parsing?

E.g., why is *ident* considered to be a terminal symbol and not a nonterminal symbol?



# *Why is Scanning not Part of Parsing?*

## **It would make parsing more complicated**

(e.g. difficult distinction between keywords and identifiers)

```
Statement = ident "=" Expr ";"  
           | "if" "(" Expr ")" ... .
```

One would have to write this as follows:

```
Statement = "i" ( "f" "(" Expr ")" ...  
               | notF {letter | digit} "=" Expr ";"  
               )  
           | notI {letter | digit} "=" Expr ";".
```

## **The scanner must eliminate blanks, tabs, end-of-line characters and comments**

(these characters can occur anywhere => would lead to very complex grammars)

```
Statement = "if" {Blank} "(" {Blank} Expr {Blank} ")" {Blank} ... .  
Blank = " " | "\r" | "\n" | "\t" | Comment.
```

## **Tokens can be described with regular grammars**

(simpler and more efficient than context-free grammars)



## 2. Lexical Analysis

2.1 Tasks of a Scanner

2.2 Regular Grammars and Finite Automata

2.3 Scanner Implementation



# Regular Grammars

## Definition

A grammar is called regular if it can be described by productions of the form:

$$\begin{array}{l}
 X = a. \quad a, b \hat{\in} TS \\
 X = b Y. \quad X, Y \hat{\in} NTS
 \end{array}$$

## Example Regular grammar for identifiers

Ident = letter.  
 Ident = letter Rest.  
 Rest = letter.  
 Rest = digit.  
 Rest = '\_' .  
 Rest = letter Rest.  
 Rest = digit Rest.  
 Rest = '\_' Rest.

e.g., derivation of the name xy3

Ident  $\vdash$  letter Rest  $\vdash$  letter letter Rest  $\vdash$  letter letter digit

## Alternative definition

A grammar is called regular if it can be described by a single non-recursive EBNF production.

## Example Regular grammar for identifiers

Ident = letter {letter | digit | '\_' }.

# Examples



**Can we transform the following grammar into a regular grammar?**

$E = T \{ "+" T \}.$   
 $T = F \{ "*" F \}.$   
 $F = \text{id}.$

**Can we transform the following grammar into a regular grammar?**

$E = F \{ "*" F \}.$   
 $F = \text{id} \mid "(" E ")".$



# Limitations of Regular Grammars

## Regular grammars cannot deal with *nested structures*

because they cannot handle *central recursion*!

But central recursion is important in most programming languages

- nested expressions      **Expr**  $\rightarrow$  \* ... "(" Expr ")" ...
- nested statements      **Statement**  $\rightarrow$  "do" **Statement** "while" "(" Expr ")"
- nested classes      **Class**  $\rightarrow$  "class" "{" ... **Class** ... "}"

For productions like these we need context-free grammars

## But most lexical structures are regular

identifiers	letter {letter   digit}
numbers	digit {digit}
strings	"\" {noQuote} "\"
keywords	letter {letter}
operators	">" "="

## Exception: nested comments

`/* ..... /* ... */ ..... */`

The scanner must treat them in a special way




# Deterministic Finite Automaton (DFA)



Can be used to analyze regular languages

## Example



⊙ final state  
start state is always state 0 by convention

State transition function as a table

d	letter	digit
s0	s1	error
s1	s1	s1

"finite", because d can be written down explicitly

## Definition

A deterministic finite automaton is a 5 tuple  $(S, I, d, s_0, F)$

- $S$  set of states
- $I$  set of input symbols
- $d: S \times I \rightarrow S$  state transition function
- $s_0$  start state
- $F$  set of final states


The **language** recognized by a DFA is the set of all symbol sequences that lead from the start state into one of the final states

A DFA has recognized a sentence

- if it is in a final state
- and if the input is totally consumed or there is no possible transition with the next input symbol

# The Scanner as a DFA

The scanner can be viewed as a big DFA



**Example** input: max >= 30

$s_0 \xrightarrow{m} s_1 \xrightarrow{a} s_1 \xrightarrow{x} s_1$

- no transition with " " in  $s_1$
- *ident* recognized

$s_0 \xrightarrow{" " } s_0 \xrightarrow{>} s_4 \xrightarrow{=} s_5$

- skips blanks at the beginning
- does not stop in  $s_4$
- no transition with " " in  $s_5$
- *geq* recognized

$s_0 \xrightarrow{" " } s_0 \xrightarrow{3} s_2 \xrightarrow{0} s_2$

- skips blanks at the beginning
- no transition with " " in  $s_2$
- *number* recognized

After every recognized token the scanner starts in  $s_0$  again

## 2. Lexical Analysis

2.1 Tasks of a Scanner

2.2 Regular Grammars and Finite Automata

2.3 Scanner Implementation

# Scanner Interface



```
class Scanner {  
    static void    init (Reader r) {...}  
    static Token  next () {...}  
}
```

For efficiency reasons methods are static  
(there is just one scanner per compiler)

## Example: Initializing the scanner

```
InputStream s = new FileInputStream("myfile.mj");  
Reader r = new InputStreamReader(s);  
Scanner.init(r);
```

## Example: Reading the token stream

```
for (;;) {  
    Token t = Scanner.next();  
    ...  
}
```

# Tokens



```
class Token {
    int kind;      // token code
    int line;     // token line (for error messages)
    int col;      // token column (for error messages)
    int val;      // token value (for number and charCon)
    String string; // token string
}
```

## Token codes for MicroJava

<u>error token</u>	<u>token classes</u>	<u>operators and special characters</u>		<u>keywords</u>	<u>end of file</u>
static final int none = 0,	ident = 1, number = 2, charCon = 3,	plus = 4, /* + */ minus = 5, /* - */ times = 6, /* * */ slash = 7, /* / */ rem = 8, /* % */ eql = 9, /* == */ neq = 10, /* != */ lss = 11, /* < */ leq = 12, /* <= */ gtr = 13, /* > */ geq = 14, /* >= */	assign = 15, /* = */ semicolon = 16, /* ; */ comma = 17, /* , */ period = 18, /* . */ lpar = 19, /* ( */ rpar = 20, /* ) */ lbrack = 21, /* [ */ rbrack = 22, /* ] */ lbrace = 23, /* { */ rbrace = 24, /* } */	class_ = 25, else_ = 26, final_ = 27, if_ = 28, new_ = 29, print_ = 30, program_ = 31, read_ = 32, return_ = 33, void_ = 34, while_ = 35,	eof = 36;



# Scanner Implementation

## Static fields in class *Scanner*

```
static Reader in;           // input stream
static char ch;           // next input character (still unprocessed)
static int line, col;     // line and column number of the character ch
static final int eofCh = '\u0080'; // character that is returned at the end of the file
```

## **init()**

```
public static void init (Reader r) {
    in = r;
    line = 1; col = 0;
    nextCh(); // reads the first character into ch and increments col to 1
}
```

## **nextCh()**

```
private static void nextCh() {
    try {
        ch = (char) in.read(); col++;
        if (ch == '\n') { line++; col = 0; }
        else if (ch == '\uffff') ch = eofCh;
    } catch (IOException e) { ch = eofCh; }
}
```

- *ch* = next input character
- returns *eofCh* at the end of the file
- increments *line* and *col*

## *next()*

```

public static Token next() {
    while (ch <= ' ') nextCh(); // skip blanks, tabs, eols
    Token t = new Token(); t.line = line; t.col = col;
    switch (ch) {
        case 'a': case 'b': ... case 'z': case 'A': case 'B': ... case 'Z':
            readName(t); break;
        case '0': case '1': ... case '9':
            readNumber(t); break;
        case ';': nextCh(); t.kind = semicolon; break;
        case '.': nextCh(); t.kind = period; break;
        case eofCh: t.kind = eof; break; // no nextCh() any more
        ...
        case '=': nextCh();
            if (ch == '=') { nextCh(); t.kind = eql; } else t.kind = assign;
            break;
        ...
        case '/': nextCh();
            if (ch == '/') {
                do nextCh(); while (ch != '\n' && ch != eofCh);
                t = next(); // call scanner recursively
            } else t.kind = slash;
            break;
        default: nextCh(); t.kind = none; break;
    }
    return t;
} // ch holds the next character that is still unprocessed

```

} names, keywords  
 } numbers  
 } simple tokens  
 } compound tokens  
 } comments  
 } invalid character



## Further Methods

### **private static void readName(Token t)**

- At the beginning *ch* holds the first letter of the name
- Reads further letters and digits and stores them in *t.string*
- Looks up the name in a keyword table (using hashing or binary search)  
if found:            *t.kind = token number of the keyword;*  
otherwise:         *t.kind = ident;*
- At the end *ch* holds the first character after the name

### **private static void readNumber(Token t)**

- At the beginning *ch* holds the first digit of the number
- Reads further digits, converts them into a number and stores the number value to *t.val*.  
if overflow:        report an error
- *t.kind = number;*
- At the end *ch* holds the first character after the number





## Further Methods

### **private static void readCharCon(Token t)**

- At the beginning *ch* holds a single quote
- Reads further characters and stores them in *t.string*
- At the end *ch* holds the first character after the closing quote
- Sets the following token fields:
  - t.kind = charCon;
  - t.val = *numeric char value*;

#### *valid char constants*

'x'  
'\r'  
'\n'  
'\t'

#### *invalid char constants*

'xy'  
"  
'x'  
↑

Scanner reports an error,  
but returns a *charCon*



## *What you should do in the lab*

1. Study the specification of MicroJava carefully (Appendix A of the handouts).
2. Create a package *MJ*;  
Download *Scanner.java* and *Token.java* from <http://ssw.jku.at/Misc/CC/> into this package.  
Try to understand what they do.
3. Complete *Scanner.java* according to the slides of the course;  
Compile *Token.java* and *Scanner.java*.
4. Download *TestScanner.java* into the package *MJ* and compile it.
5. Download the MicroJava source program *sample.mj* and run *TestScanner* on it.
6. Download the MicroJava source program *BuggyScannerInput.mj* and run *TestScanner* on it